
The **Sunbury** fabric awning creates year-round shelter and beauty for the doors and windows of your home or business. The **Sunbury Awning** features a unique frame system which provides continuous concealed



attachment of the fabric to the frame. Fabric Awnings have a natural inviting warmth which few other building materials can achieve. **Proline Fabric Awnings** are custom made to conform to most any building and feature rigid welded structural metal frames with architectural fabrics specifically designed for exterior use.





QUEEN CITY AWNING



7225 East Kemper Road Cincinnati Ohio 45249 local: 513-530-9660 Dayton: 937-222-7670 nationwide: 800-611-2800 fax: 513-530-0662

QueenCityAwning.com

SPECIFICATIONS:

Series: PROLINE

Style: Sunbury fabric awning as manufactured by Queen City Awning Cincinnati, Ohio

Size: Specify width up to 10'-0", height up to 3'-0" and projection up to 5'-0".

Fabric: Specify type and/or brand.

<u>Canvas -</u> Woven acrylic fabric is U.V. and mildew resistant and water repellent. Available in solid colors and striped patterns. Some solids and patterns available in a flame resistant series.

VINYL - Laminated or coated polyester fabric is U.V. and mildew resistant and water repellent. Available in solid colors and with protective coatings. Also available in translucent colors for backlighting. Most vinyl fabrics are flame resistant, consult factory.

Frame:

ALUMINUM - Fabri-Frame aluminum extrusion system. Mill finish square and rectangular shapes of 6063-T6 alloy. Connections are welded and cleaned. Fabric staples into frame slot and is covered with a PVC insert. Specify color of insert.

Mounting: Awning and canopy frames are furnished with wall brackets for mounting to masonry, wood and E.I.F.S.

Graphics: Lettering and signage can be applied to fabrics in a variety of methods. Surface applied graphics for non-backlit applications and translucent graphics for backlit applications.

Specifications subject to change without notice. Consult factory for any unique requirements.